



CABLE TIE EXPRESS

PROUDLY CELEBRATING


TYING SERVICE TO QUALITY SINCE 1995

expandable sleeving and split wrap



polyester expandable sleeving

- constructed from durable polyester material
- abrasion resistance for industrial applications
- open weave for easy install of cables and hoses
- expands to 1.5x capacity
- wide operating temperature range of -50°C to +150°C
- 0.125" to 3" diameter available



polyester braided split wrap

- constructed from durable polyester material
- self-closing wrap for ease of installation and inspection
- open structure allows for installation after components
- tough, resilient construction
- wide operating temperature range of -40°C to +150°C
- 0.2" to 1.5" diameter available



polyester woven split wrap

- constructed from woven mono- and multifilament polyester material
- cost effective, non-expanding lightweight construction offering high levels of flexibility
- self-closing for installation on completed assemblies
- wide operating temperature range of -40°C to +150°C
- 0.125" to 2" diameter available



TEL 888-603-1233 EMAIL sales@cabletieexpress.com

cabletieexpress.com

Pegasus
SUPPLY GROUP

technical specifications




polyester expandable sleeving

PART NUMBER	STANDARD COLOR	SIZE	WIDTH	ID MINIMUM	ID MAXIMUM	BUNCHES	FILAMENTS PER BUNCH	FILAMENT DIAMETER	LENGTH PER ROLL
CBPETBS1/8BK1650	BLACK	1/8"	0.12" ± 0.04"	0.08"	0.28"	24	3	0.008"	1650 ft
CBPETBS1/4BK1650	BLACK	1/4"	0.24" ± 0.04"	0.12"	0.35"	32	3	0.008"	1650 ft
CBPETBS5/16BK1650	BLACK	5/16"	0.31" ± 0.08"	0.20"	0.51"	40	3	0.008"	1650 ft
CBPETBS3/8BK1650	BLACK	3/8"	0.39" ± 0.08"	0.24"	0.63"	48	3	0.008"	1650 ft
CBPETBS1/2BK825	BLACK	1/2"	0.47" ± 0.08"	0.28"	0.75"	56	3	0.008"	825 ft
CBPETBS5/8BK825	BLACK	5/8"	0.59" ± 0.08"	0.35"	0.87"	48	3	0.010"	825 ft
CBPETBS3/4BK825	BLACK	3/4"	0.71" ± 0.08"	0.47"	0.98"	56	3	0.010"	825 ft
CBPETBS1BK825	BLACK	1"	0.98" ± 0.12"	0.63"	1.26"	72	3	0.010"	825 ft
CBPETBS1-1/4BK330	BLACK	1-1/4"	1.18" ± 0.12"	0.79"	1.69"	96	3	0.010"	330 ft
CBPETBS1-1/2BK330	BLACK	1-1/2"	1.57" ± 0.12"	0.98"	1.89"	96	4	0.010"	330 ft
CBPETBS1-3/4BK330	BLACK	1-3/4"	1.97" ± 0.20"	1.18"	2.36"	120	4	0.010"	330 ft
CBPETBS2BK330	BLACK	2"	2.36" ± 0.20"	1.57"	2.76"	120	5	0.010"	330 ft
CBPETBS2-1/2BK165	BLACK	2-1/2"	2.76" ± 0.20"	1.77"	3.15"	120	6	0.010"	165 ft
CBPETBS3BK165	BLACK	3"	3.15" ± 0.20"	1.97"	3.54"	120	7	0.010"	165 ft



polyester braided split wrap

PART NUMBER	STANDARD COLOR	SIZE	NORMAL BUNDLE DIA.	MAXIMUM BUNDLE DIA.	LENGTH PER ROLL
CBPETNSCG1/5BK330	BLACK	1/5"	0.20"	0.24"	330 ft
CBPETNSCG5/16BK330	BLACK	5/16"	0.31"	0.35"	330 ft
CBPETNSCG3/8BK330	BLACK	3/8"	0.39"	0.43"	330 ft
CBPETNSCG1/2BK330	BLACK	1/2"	0.51"	0.55"	330 ft
CBPETNSCG5/8BK330	BLACK	5/8"	0.63"	0.67"	330 ft
CBPETNSCG3/4BK165	BLACK	3/4"	0.75"	0.79"	165 ft
CBPETNSCG1BK165	BLACK	1"	0.98"	1.06"	165 ft
CBPETNSCG1-1/9BK82	BLACK	1-1/9"	1.14"	1.22"	82 ft
CBPETNSCG1-1/4BK82	BLACK	1-1/4"	1.26"	1.34"	82 ft
CBPETNSCG1-1/2BK82	BLACK	1-1/2"	1.50"	1.57"	82 ft



polyester woven split wrap

PART NUMBER	STANDARD COLOR	SIZE	NORMAL BUNDLE DIA.	MAXIMUM BUNDLE DIA.	WIDTH	LENGTH PER ROLL
CBPETSCG1/8BK330	BLACK	1/8"	0.12"	0.16"	0.87" ± 0.08"	330 ft
CBPETSCG1/5BK330	BLACK	1/5"	0.20"	0.24"	1.18" ± 0.08"	330 ft
CBPETSCG5/16BK330	BLACK	5/16"	0.31"	0.35"	1.57" ± 0.08"	330 ft
CBPETSCG3/8BK330	BLACK	3/8"	0.39"	0.47"	1.97" ± 0.08"	330 ft
CBPETSCG1/2BK330	BLACK	1/2"	0.51"	0.59"	2.44" ± 0.12"	330 ft
CBPETSCG5/8BK330	BLACK	5/8"	0.63"	0.71"	3.15" ± 0.12"	330 ft
CBPETSCG3/4BK165	BLACK	3/4"	0.75"	0.87"	4.13" ± 0.12"	165 ft
CBPETSCG1BK165	BLACK	1"	1.00"	1.06"	5.04" ± 0.16"	165 ft
CBPETSCG1-1/4BK82	BLACK	1-1/4"	1.18"	1.30"	5.91" ± 0.16"	82 ft
CBPETSCG1-1/2BK82	BLACK	1-1/2"	1.50"	1.65"	7.48" ± 0.20"	82 ft
CBPETSCG2BK82	BLACK	2"	1.97"	2.17"	9.84" ± 0.20"	82 ft