

# hook and loop fastening ties

- back to back design provides fast and easy application
- constructed with high quality nylon hook and polypropylene loop
- operating temp range from -20°C to + 85°C (-40°F to + 185°F)
- high chemical resistance- operates with alkaline soda, ammonia, nitric acid or hydrochloric acid present
- flammability rating to UL 94 HB
- lamination (opening) strength  $\geq 2.5$  Kg
- breaking strength minimum 175 N/cm
- stocked in standard black color



## hook & loop - strap ties

PART NUMBER	COLOR	LENGTH	WIDTH	BAG QTY
HL-5-1/2-BK-100	BLACK	5.0"	0.50"	100
HL-8-1/2-BK-100	BLACK	8.0"	0.50"	100
HL-12-1/2-BK-100	BLACK	12.0"	0.50"	100
HL-6-3/4-BK-100	BLACK	6.0"	0.75"	100
HL-8-3/4-BK-100	BLACK	8.0"	0.75"	100
HL-12-3/4-BK-100	BLACK	12.0"	0.75"	100
HL-18-3/4-BK-100	BLACK	18.0"	0.75"	100



## hook & loop - bulk roll

PART NUMBER	COLOR	WIDTH	ROLL LENGTH
HL-1/2-BK-25YD	BLACK	0.50"	25YD
HL-3/4-BK-25YD	BLACK	0.75"	25YD

high quality and durable hook and loop fasteners in a variety of lengths for all applications